


# Three Phase Hybrid Inverter

SUN-10-SG01HP3-EU-DM2



- 100** 100% unbalanced output
-  AC couple to retrofit existing solar system
- 10** \*Max. 10 pcs parallel for on-grid and off-grid operation; Support multiple batteries parallel
- 37** Max. charging/discharging current of 37A
- H** High voltage battery, higher efficiency
- 6** 6 time periods for battery charging/discharging
-  Support storing energy from diesel generator

**Deye**

Stock Code: 605117.SH

Model		SUN-10K-SG01HP3 -EU-DM2
<b>Battery Input Data</b>		
Battery Type	Lithium-ion	
Battery Voltage Range (V)	160-700	
Max. Charging Current (A)	37	
Max. Discharging Current (A)	37	
Charging Strategy for Li-ion Battery	Self-adaption to BMS	
Number of Battery Input	1	
<b>PV String Input Data</b>		
Max. PV Access Power (W)	20000	
Max. PV Input Power (W)	16000	
Max. PV Input Voltage (V)	1000	
Start-up Voltage (V)	180	
MPPT Voltage Range (V)	150-850	
Rated PV Input Voltage (V)	600	
Max. Operating PV Input Current (A)	18+18	
Max. Input Short-Circuit Current (A)	27+27	
No. of MPP Trackers/ No. of Strings MPP Tracker	2/1+1	
<b>AC Input/Output Data</b>		
Rated AC Input/Output Active Power (W)	10000	
Max. AC Input/Output Apparent Power (VA)	11000	
Rated AC Input/Output Current (A)	15.2/14.5	
Max. AC Input/Output Current (A)	16.7/16	
Max. Continuous AC Passthrough (grid to load) (A)	35	
Peak Power (off-grid) (W)	1.5 times of rated power, 10s	
Power Factor Adjustment Range	0.8 leading to 0.8 lagging	
Rated Input/Output Voltage/Range (V)	220/380V, 230/400V 0.85Un-1.1Un	
Rated Input/Output Grid Frequency/Range(Hz)	50/45-55, 60/55-65	
Grid Connection Form	3L+N+PE	
Total Current Harmonic Distortion THDi	<3% (of nominal power)	
DC Injection Current	<0.5% In	
<b>Efficiency</b>		
Max. Efficiency	97.6%	
Euro Efficiency	97.0%	
MPPT Efficiency	>99%	
<b>Equipment Protection</b>		
Integrated	DC Reverse Polarity Protection, AC Output Overcurrent Protection, Thermal Protection, AC Output Overvoltage Protection, AC Output Short Circuit Protection, DC Component Monitoring, Arc Fault Circuit Interrupter (optional), Anti-islanding Protection, DC Switch, Insulation Impedance Detection, Residual Current Detection	
Surge Protection Level	TYPE II(DC), TYPE II(AC)	
<b>Interface</b>		
Communication Interface	WIFI, RS485, CAN	
<b>General Data</b>		
Operating Temperature Range (°C)	-40 to +60°C, >45°C Derating	
Permissible Ambient Humidity	0-100%	
Permissible Altitude	2000m	
Noise (dB)	≤45	
Ingress Protection(IP) Rating	IP 65	
Inverter Topology	Non-Isolated	
Over Voltage Category	OVC II(DC), OVC III(AC)	
Cabinet Size (WxHxD mm)	376×470×244.5 (Excluding Connectors and Brackets)	
Weight (kg)	24	
Type of Cooling	Natural Cooling	
Warranty	5 Years/10 Years the Warranty Period Depends the Final Installation Site of Inverter, More Info Please Refer to Warranty Policy	
Grid Regulation	IEC 61727, IEC 62116, CEI 0-21, EN 50549, NRS 097, RD 140, UNE 217002, OVE-Richtlinie R25, G98, G99, VDE-AR-N 4105	
Safety / EMC Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2	